

'protecting your premises'

from unwanted intruders with our Video Door Phones

Sales/Support - 1300NEVRAS

- ACCESS CONTROL SYSTEMS - BUILDING INTERCOMS - CCTV SURVEILLANCE SYSTEMS - SECURITY ALARM SYSTEMS - VIDEO DOOR PHONES -

Video Door Phone with Video & Photo Recording

Product Code: ITS-VIDINT-005

Indoor Monitor - Specifications:

- 7 inch TFT LCD display (16:9); Hands-free video intercom
- Intercommunication between internal indoor monitors
- Support key-unlock, call transfer to other extension, surveillance and monitoring
- Semi-duplex audio communication mode
- Support photo capture & video record: manual and automatic mode
- Support photo browse, music and video playback
- USB interface & additional SD card available with 2GB max
- Built in flash memory with 128MB
- Support download/upload media files including MP3, WAV, WMA, JPEG via USB interface
- Allows selection any of audio files as a melody ring
- Up to 4 video indoor monitors can be connected with 2 outdoor cameras
- Installation method is surface-mounted
- Adjustable volume of melody ring and volume
- Brightness and chroma can be adjusted



Video Outdoor Unit - Choose one of the following:

ITS-VIDOUT004

- Power source: DC 12V
- Camera: 1/4inch pinhole CCD
- Illumination: 0.1 Lux
- Light source: 6 Infrared LED's
- Keypad with blue LED backlight for night operation
- Operating temp: -10~ +60°
- Installation: wall or flush mounted
- Material: Anti-oxidation aluminium alloy panel
- IP 55 waterproof and dustproof outdoor unit

ITS-VIDOUT005

- Power source: DC 12V
- Camera: 1/3inch pinhole CCD
- Illumination: 0.1 Lux
- Light source: 6 Infrared LED's
- Keypad with blue LED backlight for night operation
- Operating temp: -40~ +60°
- Installation: wall or flush mounted
- Material: Anti-oxidation aluminium alloy panel
- IP 55 waterproof and dustproof outdoor unit

ITS-VIDOUT006

- Power source: DC 12V
- Camera: 1/4 inch CCD
- Illumination: 0.1 Lux
- Light source: 6 Infrared LED's
- Keypad with blue LED backlight for night operation
- Tilt control allows the camera angle to be moved up and down at ±15°visual angle
- Operating temp: -10~ +60°
- Installation: wall mounted
- Material: Plastic panel
- IP 55 waterproof and dustproof outdoor unit







Electric Door Strikes and Electronic Gate Locks are also available